



Technische Daten

JIC-Anschlussstutzen, 74°-Konus mit UN-/UNF-Gewinde

Material:
Automatenstahl
Oberfläche:
CrIII

Technical data

JIC threaded adapter, 74° cone with UN/UNF thread

Material:
Free cutting steel
Surface:
CrIII

DN Nominal width	Size Size	Zoll Inch	Anschluss T Thread T	Abzugsmaß C (mm) Cut-off C (mm)	d (mm) d (mm)	E (mm) E (mm)	L (mm) L (mm)	VE PU	Artikelnummer Article number
6	04	1/4	7/16-20	26,5	4,0	12	54,0	5	VC07JM04
6	04	1/4	1/2-20	27,0	4,0	14	52,0	5	VC08JM04
6	04	1/4	9/16-18	27,0	4,0	15	52,0	5	VC09JM04
8	05	5/16	9/16-18	28,0	5,5	15	54,5	5	VC09JM05
10	06	3/8	9/16-18	30,5	7,0	17	59,5	5	VC09JM06
10	06	3/8	3/4-16	30,0	7,0	19	59,5	5	VC12JM06
10	06	3/8	7/8-14	36,0	7,0	24	63,5	5	VC14JM06
12	08	1/2	3/4-16	31,0	9,5	19	62,5	5	VC12JM08
12	08	1/2	7/8-14	35,0	9,5	24	66,5	5	VC14JM08
12	08	1/2	1.1/16-12	37,0	9,5	27	68,5	5	VC17JM08
16	10	5/8	7/8-14	35,0	12,0	24	69,5	5	VC14JM10
16	10	5/8	1.1/16-12	37,0	12,0	27	71,5	5	VC17JM10
19	12	3/4	1.1/16-12	38,0	15,0	27	87,5	5	VC17JM12
19	12	3/4	1.3/16-12	41,0	15,0	32	90,5	5	VC19JM12
19	12	3/4	1.5/16-12	42,0	15,0	34	91,5	5	VC21JM12
25	16	1	1.5/16-12	43,0	20,0	34	96,5	1	VC21JM16
25	16	1	1.5/8-12	48,5	20,0	42	99,5	1	VC26JM16

Standardnennweiten in **Fettdruck**, standard dimensions in **bold print**