



Technische Daten

BSP-Anschlussstutzen, 60°-Konus mit BSP Außengewinde

Material:
Automatenstahl

Oberfläche:
Grill

Technical data

BSP-threaded adapter, 60°-cone with BSP male thread

Material:
Free cutting steel

Surface:
Grill

DN Nominal width	Size Size	Zoll Inch	Anschluss T Thread T	Abzugsmaß C (mm) Cut-off C (mm)	d (mm) d (mm)	E (mm) E (mm)	L (mm) L (mm)	VE PU	Artikelnummer Article number
6	04	1/4	1/8-28	21,0	4,0	14	46,0	5	VC02BM04
6	04	1/4	1/4-19	26,0	4,0	19	54,4	5	VC04BM04
6	04	1/4	3/8-19	28,0	4,0	22	53,0	5	VC06BM04
8	05	5/16	1/4-19	27,0	5,5	19	54,5	5	VC04BM05
8	05	5/16	3/8-19	28,0	5,5	22	55,5	5	VC06BM05
10	06	3/8	3/8-19	29,0	7,0	22	58,5	5	VC06BM06
10	06	3/8	1/2-14	32,0	7,0	27	61,5	5	VC08BM06
12	08	1/2	3/8-19	29,0	9,5	22	60,5	5	VC06BM08
12	08	1/2	1/2-14	33,0	9,5	27	64,5	5	VC08BM08
12	08	1/2	3/4-14	35,5	9,5	32	66,5	5	VC12BM08
16	10	5/8	1/2-14	33,0	12,0	27	67,5	5	VC08BM10
16	10	5/8	5/8-14	34,0	12,0	30	68,5	5	VC10BM10
16	10	5/8	3/4-14	33,5	12,0	32	69,5	5	VC12BM10
19	12	3/4	3/4-14	36,0	15,0	32	75,0	5	VC12BM12
19	12	3/4	1-11	39,0	15,0	41	88,5	1	VC16BM12
25	16	1	1-11	40,0	20,0	41	93,5	1	VC16BM16

Standardnennweiten in **Fettdruck**, standard dimensions in **bold print**