



## Technische Daten

JIC-Dichtkopf, 74°-Konus mit Überwurfmutter, UN-/UNF-Gewinde

**Material:**  
Automatenstahl

**Oberfläche:**  
Grill

## Technical data

JIC threaded adapter, 74° cone with union nut, UN/UNF thread

**Material:**  
Free cutting steel

**Surface:**  
Grill

DN Nominal width	Size Size	Zoll Inch	Anschluss T Thread T	Abzugsmaß C (mm) Cut-off C (mm)	d (mm) d (mm)	E (mm) E (mm)	H (mm) H (mm)	L (mm) L (mm)	VE PU	Artikelnummer Article number
<b>6</b>	<b>04</b>	<b>1/4</b>	<b>7/16-20</b>	<b>25,0</b>	<b>4,0</b>	<b>15</b>	<b>24,0</b>	<b>50,0</b>	<b>5</b>	<b>VC07J90S04</b>
6	04	1/4	1/2-20	31,0	4,0	17	29,5	59,0	5	VC08J90S04
6	04	1/4	9/16-18	27,0	4,0	19	26,0	52,0	5	VC09J90S04
8	05	5/16	9/16-18	28,0	5,5	19	30,0	56,0	5	VC09J90S05
<b>10</b>	<b>06</b>	<b>3/8</b>	<b>9/16-18</b>	<b>30,0</b>	<b>7,0</b>	<b>19</b>	<b>34,0</b>	<b>59,5</b>	<b>5</b>	<b>VC09J90S06</b>
10	06	3/8	3/4-16	33,0	7,0	24	33,0	62,5	5	VC12J90S06
<b>12</b>	<b>08</b>	<b>1/2</b>	<b>3/4-16</b>	<b>39,0</b>	<b>9,5</b>	<b>24</b>	<b>38,0</b>	<b>70,5</b>	<b>5</b>	<b>VC12J90S08</b>
12	08	1/2	7/8-14	42,0	9,5	27	42,0	73,5	5	VC14J90S08
<b>16</b>	<b>10</b>	<b>5/8</b>	<b>7/8-14</b>	<b>44,0</b>	<b>12,0</b>	<b>27</b>	<b>47,0</b>	<b>78,5</b>	<b>5</b>	<b>VC14J90S10</b>
<b>16</b>	<b>10</b>	<b>5/8</b>	<b>1.1/16-12</b>	<b>45,0</b>	<b>12,0</b>	<b>32</b>	<b>45,0</b>	<b>79,5</b>	<b>5</b>	<b>VC17J90S10</b>
19	12	3/4	7/8-14	56,0	15,0	32	53,0	95,0	5	VC14J90S12
19	12	3/4	1.1/16-12	56,0	15,0	36	53,0	105,5	5	VC17J90S12
25	16	1	7/8-14	70,0	20,0	38	65,0	123,5	1	VC14J90S16

Standardnennweiten in **Fettdruck**, standard dimensions in **bold print**