



## Technische Daten

JIC-Dichtkopf, 74°-Konus mit Überwurfmutter, UN-/UNF-Gewinde

**Material:**  
Automatenstahl

**Oberfläche:**  
Grill

## Technical data

JIC threaded adapter, 74° cone with union nut, UN-/UNF thread

**Material:**  
Free cutting steel

**Surface:**  
Grill

DN Nominal width	Size Size	Zoll Inch	Anschluss T Thread T	Abzugsmaß C (mm) Cut-off C (mm)	d (mm) d (mm)	E (mm) E (mm)	L (mm) L (mm)	VE PU	Artikelnummer Article number
<b>6</b>	<b>04</b>	<b>1/4</b>	<b>7/16-20</b>	<b>13,0</b>	<b>4,0</b>	<b>15</b>	<b>40,0</b>	<b>5</b>	<b>VC07JF04</b>
6	04	1/4	1/2-20	15,0	4,0	17	40,0	5	VC08JF04
6	04	1/4	9/16-18	16,0	4,0	19	41,0	5	VC09JF04
<b>8</b>	<b>05</b>	<b>5/16</b>	<b>1/2-20</b>	<b>15,0</b>	<b>5,5</b>	<b>17</b>	<b>42,5</b>	<b>5</b>	<b>VC08JF05</b>
8	05	5/16	9/16-18	16,0	5,5	19	43,5	5	VC09JF05
<b>10</b>	<b>06</b>	<b>3/8</b>	<b>9/16-18</b>	<b>16,0</b>	<b>7,0</b>	<b>19</b>	<b>45,5</b>	<b>5</b>	<b>VC09JF06</b>
10	06	3/8	3/4-16	16,0	7,0	24	45,5	5	VC12JF06
<b>12</b>	<b>08</b>	<b>1/2</b>	<b>3/4-16</b>	<b>17,0</b>	<b>9,5</b>	<b>24</b>	<b>48,5</b>	<b>5</b>	<b>VC12JF08</b>
12	08	1/2	7/8-14	19,0	9,5	27	50,5	5	VC14JF08
12	08	1/2	1.1/16-12	21,0	9,5	32	53,0	5	VC17JF08
<b>16</b>	<b>10</b>	<b>5/8</b>	<b>7/8-14</b>	<b>19,0</b>	<b>12,0</b>	<b>27</b>	<b>53,5</b>	<b>5</b>	<b>VC14JF10</b>
<b>16</b>	<b>10</b>	<b>5/8</b>	<b>1.1/16-12</b>	<b>22,0</b>	<b>12,0</b>	<b>32</b>	<b>56,0</b>	<b>5</b>	<b>VC17JF10</b>
19	12	3/4	1.1/16-12	20,0	15,0	32	69,5	5	VC17JF12
<b>19</b>	<b>12</b>	<b>3/4</b>	<b>1.3/16-12</b>	<b>24,5</b>	<b>15,0</b>	<b>36</b>	<b>65,5</b>	<b>5</b>	<b>VC19JF12</b>
19	12	3/4	1.5/16-12	21,0	15,0	38	70,5	5	VC21JF12
<b>25</b>	<b>16</b>	<b>1</b>	<b>1.5/16-12</b>	<b>22,0</b>	<b>20,0</b>	<b>38</b>	<b>75,5</b>	<b>1</b>	<b>VC21JF16</b>

Standardnennweiten in **Fettdruck**, standard dimensions in **bold print**