



Technische Daten

BSP-Dichtkopf, 60°-Konus mit Überwurfmutter, BSP-Gewinde

Material:
Automatenstahl

Oberfläche:
CrIII

Technical data

BSP sealing head, 60° cone with union nut, BSP thread

Material:
Free cutting steel

Surface:
CrIII

DN Nominal width	Size Size	Zoll Inch	Anschluss T Thread T	Abzugsmaß C (mm) Cut-off C (mm)	d (mm) d (mm)	E (mm) E (mm)	H (mm) H (mm)	L (mm) L (mm)	VE PU	Artikelnummer Article number
6	04	1/4	1/4-19	40,0	4,0	19	16,0	65,0	5	VC04B45S04
6	04	1/4	3/8-19	43,0	4,0	22	20,0	68,0	5	VC06B45S04
8	05	5/16	3/8-19	52,0	5,5	22	21,0	80,5	5	VC06B45S05
10	06	3/8	3/8-19	48,0	7,0	22	19,0	76,0	5	VC06B45S06
10	06	3/8	1/2-14	41,0	7,0	27	22,0	70,5	5	VC08B45S06
12	08	1/2	1/2-14	50,0	9,5	27	23,0	81,5	5	VC08B45S08
16	10	5/8	5/8-14	59,0	12,0	30	27,0	93,5	5	VC10B45S10
16	10	5/8	3/4-14	64,0	12,0	32	26,0	98,5	5	VC12B45S10
19	12	3/4	3/4-14	70,0	15,0	32	28,0	119,5	5	VC12B45S12
19	12	3/4	1-11	69,5	15,0	38	31,5	110,5	1	VC16B45S12
25	16	1	1-11	84,0	20,0	38	35,0	137,5	1	VC16B45S16

Standardnennweiten in **Fettdruck**, standard dimensions in **bold print**