



Technische Daten

BSP-Dichtkopf, 60°-Konus mit Überwurfmutter, BSP-Gewinde

Material:
Automatenstahl

Oberfläche:
Grill

Technical data

BSP sealing head, 60° cone with union nut, BSP thread

Material:
Free cutting steel

Surface:
Grill

| DN Nominal width | Size Size | Zoll Inch | Anschluss T Thread T | Abzugsmaß C (mm) Cut-off C (mm) | d (mm) d (mm) | E (mm) E (mm) | H (mm) H (mm) | L (mm) L (mm) | VE PU | Artikelnummer Article number |
|---------------------|--------------|--------------|-------------------------|------------------------------------|------------------|------------------|------------------|------------------|----------|---------------------------------|
| 6 | 04 | 1/4 | 1/4-19 | 25,0 | 4,0 | 19 | 28,0 | 50,0 | 5 | VC04B90S04 |
| 6 | 04 | 1/4 | 3/8-19 | 25,0 | 4,0 | 22 | 31,0 | 50,0 | 5 | VC06B90S04 |
| 8 | 05 | 5/16 | 3/8-19 | 29,0 | 5,5 | 22 | 36,0 | 56,5 | 5 | VC06B90S05 |
| 10 | 06 | 3/8 | 3/8-19 | 33,0 | 7,0 | 22 | 35,0 | 62,5 | 5 | VC06B90S06 |
| 10 | 06 | 3/8 | 1/2-14 | 33,0 | 7,0 | 27 | 37,0 | 62,5 | 5 | VC08B90S06 |
| 12 | 08 | 1/2 | 3/8-19 | 39,5 | 9,5 | 22 | 42,0 | 72,5 | 5 | VC06B90S08 |
| 12 | 08 | 1/2 | 1/2-14 | 39,0 | 9,5 | 27 | 41,0 | 70,5 | 5 | VC08B90S08 |
| 12 | 08 | 1/2 | 5/8-14 | 41,0 | 9,5 | 28 | 46,0 | 73,0 | 5 | VC10B90S08 |
| 12 | 08 | 1/2 | 3/4-14 | 39,0 | 9,5 | 32 | 44,0 | 70,5 | 5 | VC12B90S08 |
| 16 | 10 | 5/8 | 5/8-14 | 45,0 | 12,0 | 30 | 49,0 | 79,5 | 5 | VC10B90S10 |
| 16 | 10 | 5/8 | 3/4-14 | 46,5 | 12,0 | 32 | 51,5 | 81,0 | 5 | VC12B90S10 |
| 19 | 12 | 3/4 | 3/4-14 | 56,0 | 15,0 | 32 | 54,0 | 105,5 | 5 | VC12B90S12 |
| 19 | 12 | 3/4 | 1-11 | 56,0 | 15,0 | 38 | 58,0 | 105,5 | 1 | VC16B90S12 |
| 25 | 16 | 1 | 1-11 | 70,0 | 20,0 | 38 | 65,0 | 123,5 | 1 | VC16B90S16 |

Standardnennweiten in **Fettdruck**, standard dimensions in **bold print**