



## Technische Daten

BSP-Dichtkopf, 60°-Konus mit Überwurfmutter, BSP-Gewinde

**Material:**  
Automatenstahl  
**Oberfläche:**  
CrIII

## Technical data

BSP sealing head, 60° cone with union nut, BSP thread

**Material:**  
Free cutting steel  
**Surface:**  
CrIII

DN Nominal width	Size Size	Zoll Inch	Anschluss T Thread T	Abzugsmaß C (mm) Cut-off C (mm)	d (mm) d (mm)	E (mm) E (mm)	L (mm) L (mm)	VE PU	Artikelnummer Article number
6	04	1/4	1/8-28	16,0	4,0	14	41,0	5	VC02BF04
<b>6</b>	<b>04</b>	<b>1/4</b>	<b>1/4-19</b>	<b>18,0</b>	<b>4,0</b>	<b>19</b>	<b>43,0</b>	<b>5</b>	<b>VC04BF04</b>
6	04	1/4	3/8-19	20,0	4,0	22	45,0	5	VC06BF04
8	05	5/16	1/4-19	18,0	5,5	19	45,5	5	VC04BF05
<b>8</b>	<b>05</b>	<b>5/16</b>	<b>3/8-19</b>	<b>20,0</b>	<b>5,5</b>	<b>22</b>	<b>47,5</b>	<b>5</b>	<b>VC06BF05</b>
10	06	3/8	1/4-19	18,0	7,0	19	47,5	5	VC04BF06
<b>10</b>	<b>06</b>	<b>3/8</b>	<b>3/8-19</b>	<b>20,0</b>	<b>7,0</b>	<b>22</b>	<b>49,5</b>	<b>5</b>	<b>VC06BF06</b>
10	06	3/8	1/2-14	22,0	7,0	27	51,5	5	VC08BF06
12	08	1/2	3/8-19	21,0	9,0	22	54,0	5	VC06BF08
<b>12</b>	<b>08</b>	<b>1/2</b>	<b>1/2-14</b>	<b>23,0</b>	<b>9,5</b>	<b>27</b>	<b>54,5</b>	<b>5</b>	<b>VC08BF08</b>
12	08	1/2	3/4-14	25,0	9,5	32	58,0	5	VC12BF08
16	10	5/8	1/2-14	23,0	12,0	27	59,0	5	VC08BF10
<b>16</b>	<b>10</b>	<b>5/8</b>	<b>5/8-14</b>	<b>22,5</b>	<b>12,0</b>	<b>30</b>	<b>56,5</b>	<b>5</b>	<b>VC10BF10</b>
16	10	5/8	3/4-14	22,5	12,0	32	57,0	5	VC12BF10
<b>19</b>	<b>12</b>	<b>3/4</b>	<b>3/4-14</b>	<b>23,0</b>	<b>15,0</b>	<b>32</b>	<b>62,5</b>	<b>5</b>	<b>VC12BF12</b>
19	12	3/4	1-11	24,5	15,0	38	64,0	1	VC16BF12
<b>25</b>	<b>16</b>	<b>1</b>	<b>1-11</b>	<b>26,0</b>	<b>20,0</b>	<b>38</b>	<b>79,5</b>	<b>1</b>	<b>VC16BF16</b>

Standardnennweiten in **Fettdruck**, standard dimensions in **bold print**