



## Technische Daten

ORFS-Dichtform, Außengewinde mit stirnseitigem O-Ring,  
UN-/UNF-/UNS-Gewinde

**Material:**  
Automatenstahl

**Oberfläche:**  
Grill

## Technical data

ORFS Sealing form, male thread with frontal O-ring,  
UN/UNF/UNS-Thread

**Material:**  
Free cutting steel

**Surface:**  
Grill

DN Nominal width	Size Size	Zoll Inch	Anschluss T Thread T	Abzugsmaß C (mm) Cut-off C (mm)	d (mm) d (mm)	E (mm) E (mm)	L (mm) L (mm)	VE PU	Artikelnummer Article number
<b>6</b>	<b>04</b>	<b>1/4</b>	<b>9/16-18</b>	<b>32,2</b>	<b>4,0</b>	<b>15</b>	<b>48,2</b>	<b>5</b>	<b>VC04ORM04</b>
<b>10</b>	<b>06</b>	<b>3/8</b>	<b>11/16-16</b>	<b>26,2</b>	<b>7,0</b>	<b>19</b>	<b>55,7</b>	<b>5</b>	<b>VC06ORM06</b>
<b>12</b>	<b>08</b>	<b>1/2</b>	<b>13/16-16</b>	<b>29,3</b>	<b>9,5</b>	<b>22</b>	<b>60,8</b>	<b>5</b>	<b>VC08ORM08</b>
<b>16</b>	<b>10</b>	<b>5/8</b>	<b>1-14</b>	<b>33,4</b>	<b>12,0</b>	<b>27</b>	<b>67,9</b>	<b>5</b>	<b>VC10ORM10</b>
<b>19</b>	<b>12</b>	<b>3/4</b>	<b>1.3/16-12</b>	<b>35,9</b>	<b>15,0</b>	<b>32</b>	<b>75,5</b>	<b>5</b>	<b>VC12ORM12</b>
<b>25</b>	<b>16</b>	<b>1</b>	<b>1.7/16-12</b>	<b>37,4</b>	<b>20,0</b>	<b>38</b>	<b>90,9</b>	<b>1</b>	<b>VC16ORM16</b>

Standardnennweiten in **Fettdruck**, standard dimensions in **bold print**